

Datasheet

COMfortel® M-730



The tough one: designed for challenging working environments



- Robust housing for outdoor use – Ingress Protection rating 65
- Up to 13 hours of talk time – up to 320 hours of standby time
- Special function key for e.g. alarm
- Profiles for meeting, noisy environments and personal preferences
- Perfect connection: USB, Bluetooth, 3,5 mm cinch

Your advantages in detail

When working outdoors or in dusty, wet and other harsh locations, the COMfortel M-730 is the perfect choice. Due to its protection class 65 and the robust housing this handset is ideally suitable for rough all day business use. Even better now: The new COMfortel M-730 resistant to disinfectants. A long talk and standby time, seamless roaming with handover in multicell environments allow to make phone calls not only at your workplace – all day long.

Additionally, the COMfortel M-730 now offers a micro-USB connection, a 3.5 mm cinch and Bluetooth® for versatile connection possibilities. The new integrated

alarm button gives security in dangerous work areas. For alarms special tones, messages and even the location can be sent or received. It comes with a belt clip so that it can be easily taken anywhere. For a specially bustling work environments we offer the Professional Belt Clip which guarantees perfect hold.

An optimized now bigger display brings improved usability and enhances not only the readability but the productivity of the workers. Thanks to easy and audible buttons this handset can be operated with gloves or other protective equipment. A perfect companion e.g. in workshops or factories.

do you speak
FONtevo®

Features at a glance

USER INTERFACE

- Illuminated, graphical 2.4" TFT colour display, 240x320 pixels, up to 8 lines and 65.000 colours
- Intuitive, modern user interface with icons, display keys, four way navigation key, function keys and side key

AUDIO FEATURES

- HD audio supporting HDSP™/CAT-iq 2.0
- Hands free talking with excellent audio quality
- Side keys for easy volume adjustment
- 25 selectable ringer melodies with 5 volume levels and crescendo
- Vibration alarm
- Selectable audio profiles
- Headset via Bluetooth® or 3.5 mm jack

KEYPAD

- Illuminated, scratch and disinfectant resistant
- Message waiting key with blinking LED
- Separate R key
- Profile key to apply personal, silent and loud settings directly
- Side keys for easy volume adjustment
- Keylock (#-key) with PIN protection
- Special function key, e.g. for direct dialling or alarm

SECURITY

- IP65
- Solid particle protection; dust tight, no ingress of dust; complete protection against contact
- Dust-proof (incl. metal dust)
- Liquid ingress protection
- Integrated LED lamp as torch and visual alarm

QUICKSYNC SOFTWARE

- Software free to download for Windows and macOS; connection via micro USB or Bluetooth®
- Synchronise the handset directory with Microsoft Outlook®
- Upload of caller pictures / screensaver pictures
- Upload sounds (ringtones) from computer to handset
- Firmware update

- Direct dialling from Microsoft Outlook® contacts and display of incoming calls on the computer via CTI (Computer Telephony Integration) for Windows and macOS

INTERFACES

- DECT
- Bluetooth® for headset (hands free and headset profile) and for data exchange / firmware update
- vCard exchange with compatible mobile phones
- Micro-USB for charging function and data exchange / firmware update
- Headset connector 3.5 mm

ACCESSORIES

- Professional Belt Clip (optional)

NOTE

- The correct placement of the radio cells is decisive for the smooth functioning of your IP-DECT system; we therefore recommend that you leave the dimensioning and configuration to a qualified specialist dealer
- A DECT measurement can be used to determine exactly where, for example, a further basis is required to ensure supply

COMPATIBLE PRODUCTS

- 90686 / COMfortel® WS-500S
- 90687 / COMfortel® WS-500M
- 16118 / COMpact 4000
- 16119 / COMpact 4000 UK
- 16334 / COMpact 5200
- 16335 / COMpact 5200R
- 16336 / COMpact 5500R
- 16339 / COMpact 5500R UK
- 16670 / COMmander® 6000
- 16671 / COMmander® 6000R
- 16672 / COMmander® 6000RX
- 16023 / COMtrexx® Advanced
- 16022 / COMtrexx® Business
- 16021 / COMtrexx® VM

TECHNICAL SPECIFICATIONS

- Display: illuminated, graphical TFT colour display, 2.4", 128 x 160 pixels, 65,000 colours
- Radio interface: DECT/GAP, 1880-1900 MHz
- Typical range: 300 m outdoors, 50 m indoors
- Power supply: 2 batteries (NiMH) 1.2 V, 1,500 mAh max.
- Talk time: up to 13 hours
- Standby time: up to 320 hours
- Case: plastic
- Colour: anthracite
- Dimensions (w x h x d): 56 mm x 158 mm x 26 mm
- Weight Handset: approx. 166 g, incl. batteries
- Operating temperature: **+5° C to +45° C**
- Storage temperature: between -15 °C and +60 °C
- Relative Humidity: between 20 % and 75 %, non condensing
- Compliance: CE

DELIVERY

- Handset
- Battery cover
- 2 batteries (NiMH), type AAA
- Belt clip
- Rubber caps (2 of each)
- Charger
- Power adapter for charger
- Manual and security leaflet

ORDERING INFORMATION

Designation: **COMfortel® M-730**

Article number: **90243**

EAN Code: **4019377902431**